



1020-84

ISOBAR 280 CO ROCK X-HP



LABEL.SPECIFICATIONS

hose_material_reinforcement	Teräslanka	technical_workingtemperature_min	-40 °C
technical_workingtemperature_max	121 °C		

LABEL.DESRIPTION

A very flexible spiral hose for the toughest applications. With the extremely durable cover and flexibility the hose is suited in applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of SAE 100 R13. Comes in 15,2 meter rolls. Sample ferrule: 4400-09-xx (use only with 3/4" - 1") 4400-13-xx (use only with 1 1/4" - 1 1/2") 4700-04-xx (use only with 3/4" and 1") 4700-09-xx (use only with 3/4" and 1") 4700-10-xx (use only with 1 1/4" and 1 1/2")

SKU	hose_diameter_i nner	hose_dimen sion	hose_diameter_o uter	technical_workingpre ssure	hose_bendrad ius	article_weight_int ernal
10208408	13 mm	1/2"	23.8 mm	27.5 MPa	89 mm	0.7 kg
10208412	19 mm	3/4"	30.9 mm	27.5 MPa	121 mm	1.2 kg
10208416	25 mm	1"	38.2 mm	27.5 MPa	153 mm	1.8 kg