



1020-84

ISOBAR 280 CO ROCK X-HP



СПЕЦИФИКАЦИИ

hose_material_reinforcement	Stålwire	technical_workingtemperature_min	-40 °C
technical_workingtemperature_max	121 °C		

ОПИСАНИЕ

A very flexible spiral hose for the toughest applications. With the extremely durable cover and flexibility the hose is suited in applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of SAE 100 R13. Comes in 15,2 meter rolls. Sample ferrule: 4400-09-xx (use only with 3/4" - 1") 4400-13-xx (use only with 1 1/4" - 1 1/2") 4700-04-xx (use only with 3/4" and 1") 4700-09-xx (use only with 3/4" and 1") 4700-10-xx (use only with 1 1/4" and 1 1/2")

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
10208408	13 mm	1/2"	23.8 mm	27.5 MPa	89 mm	0.7 kg
10208412	19 mm	3/4"	30.9 mm	27.5 MPa	121 mm	1.2 kg
10208416	25 mm	1"	38.2 mm	27.5 MPa	153 mm	1.8 kg