



1020-85

ISOBAR 350 CO ROCK X-HP



LABEL.SPECIFICATIONS

Technické - Barva

Černý

LABEL.DESRIPTION

A very flexible spiral hose for the toughest applications. Adapted for working pressure on 420 bar. With the extremely durable cover and flexibility the hose is suited in applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of SAE 100 R15. Ferrule: 4700-04-XX (use only with 1") 4700-09-XX (use only with 1") 4700-10-XX (use only with 1 1/4" - 1 1/2")

SKU	Hadice - Vnitřní průměr	Hadice - Rozměr	Hadice - Vnější průměr	Technicko - Pracovní tlak	Hadice - Poloměr ohybu	Položka - Hmotnost - Vnitřní	Technické - Barva
10208512	19 mm	3/4"	33.3 mm	34.5 MPa	120 mm	1.6 kg	Černý
10208516	25 mm	1"	39.8 mm	34.5 MPa	157 mm	2.1 kg	Černý
10208520	32 mm	1 1/4"	51.3 mm	34.5 MPa	210 mm	3.6 kg	Černý
10208524	38 mm	1 1/2"	58.8 mm	34.5 MPa	255 mm	4.6 kg	Černý