



1020-86

ISOBAR 420 CO ROCK X-HP



LABEL.SPECIFICATIONS

Technické - Barva

Černý

LABEL.DESRIPTION

A very flexible spiral hose for the toughest applications. Adapted for working pressure on 420 bar. With the extremely durable cover and flexibility the hose is suited in applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of SAE 100 R15. Ferrule: 4700-09-XX (use only with 1") 4700-10-XX (use only with 1 1/4" - 1 1/2")

SKU	Hadice - Vnitřní průměr	Hadice - Rozměr	Hadice - Vnější průměr	Technicko - Pracovní tlak	Hadice - Poloměr ohybu	Položka - Hmotnost - Vnitřní	Technické - Barva
10208612	19 mm	3/4"	30.5 mm	42 MPa	133 mm	1.3 kg	Černý
10208616	25 mm	1"	38.7 mm	42 MPa	165 mm	2.11 kg	Černý
10208620	32 mm	1 1/4"	50 mm	42 MPa	222 mm	3.96 kg	Černý
10208624	38 mm	1 1/2"	58.1 mm	42 MPa	267 mm	5.08 kg	Černý
10208632	51 mm	2"	77.1 mm	42 MPa	660 mm	7.07 kg	Černý