



1032-0x

HYDROSCAND T1112, TWIN



СПЕЦИФИКАЦИИ

ОПИСАНИЕ

The hose is well suitable for high pressure hydraulics. The hose is also suited for high pressure gas applications, but then needs to be pin-pricked.;Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. NOTE! Air and water max +70°C

SKU	hose_diameter_i nner	hose_dimen sion	hose_diameter_o uter	technical_workingpr essure	hose_bendra dius	article_weight_int ernal
10320303	5 mm	3/16"	9.7 mm	36 MPa	30 mm	0.26 kg
10320404	6.5 mm	1/4"	11.7 mm	31 MPa	40 mm	0.33 kg
10320505	8 mm	5/16"	13.2 mm	25 MPa	55 mm	0.4 kg
10320606	10 mm	3/8"	16.5 mm	22.5 MPa	65 mm	0.44 kg
10320808	13 mm	1/2"	18.8 mm	19 MPa	85 mm	0.63 kg
10321010	16 mm	5/8"	22 mm	14 MPa	115 mm	0.67 kg
10321212	19 mm	3/4"	25.8 mm	11.5 MPa	145 mm	0.97 kg
10321616	25 mm	1"	33 mm	9.5 MPa	180 mm	1.32 kg