



1071-00

HI-TEMP



СПЕЦИФИКАЦИИ

ОПИСАНИЕ

The hose is suitable when, in standard hydraulics, there is a need for a very compact and flexible hose. Equivalent to SAE 100 R16.

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
10710004	6.5 mm	1/4"	13.5 mm	22.5 MPa	100 mm	0.23 kg
10710006	10 mm	3/8"	17.5 mm	18 MPa	125 mm	0.36 kg
10710008	13 mm	1/2"	20.6 mm	16 MPa	180 mm	0.44 kg
10710010	16 mm	5/8"	23.5 mm	13 MPa	200 mm	0.5 kg
10710012	19 mm	3/4"	27.7 mm	10.5 MPa	240 mm	0.67 kg
10710016	25 mm	1"	35.6 mm	8.8 MPa	300 mm	0.94 kg
10710020	32 mm	1 1/4"	43.5 mm	6.3 MPa	420 mm	1.14 kg
10710024	38 mm	1 1/2"	50.6 mm	5 MPa	500 mm	1.8 kg
10710032	51 mm	2"	64 mm	4 MPa	630 mm	2.01 kg