



# 1082-03

## KAPPAFLEX 2K CO ROCK



### SPECIFICATIONS

<b>Safety factor</b>	1:4	<b>Design</b>	Wrapped
<b>Temp max</b>	100 °C	<b>Color</b>	Black
<b>Temp min</b>	-40 °C	<b>Standard</b>	EN 857 2SC

### DESCRIPTION

The Kappaflex 2K CO Rock is a black hydraulic hose designed with a wrapped cover for enhanced durability. Compliant with EN 857 2SC standards, it features a single pipe construction and a safety factor of 1:4. Engineered to operate reliably in temperatures ranging from -40°C to 100°C, it ensures robust performance in demanding hydraulic applications.

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight
10820304	6.5 mm	1/4"	13.4 mm	40 MPa	50 mm	0.27 kg
1082030430	6.5 mm	1/4"	13.4 mm	40 MPa	50 mm	0.28 kg
10820305	8 mm	5/16"	14.9 mm	35 MPa	55 mm	0.33 kg
10820306	10 mm	3/8"	17.3 mm	33 MPa	65 mm	0.39 kg
1082030630	10 mm	3/8"	17.3 mm	33 MPa	65 mm	0.43 kg
10820308	13 mm	1/2"	20.3 mm	27.5 MPa	90 mm	0.49 kg
1082030830	13 mm	1/2"	20.3 mm	27.5 MPa	90 mm	0.51 kg
10820310	16 mm	5/8"	23.6 mm	25 MPa	100 mm	0.63 kg
10820312	19 mm	3/4"	27.6 mm	21.5 MPa	120 mm	0.8 kg
10820316	25 mm	1"	35.5 mm	16.5 MPa	150 mm	1.12 kg