

1092-01

P.T.F.E. HOSE



LABEL.SPECIFICATIONS

LABEL.DESCRPTION

A very suitable hose for hazardous environments together with dissolvents, paint, hydraulic oils, food as well as other applications where high temperature, high pressure and resistance towards chemicals are needed along with elastic characteristics. Age resistant. Ferrule 4200-26-xx

SKU	Hadice - Vnitřní průměr	Hadice - Rozměr	Hadice - Vnější průměr	Technicko - Pracovní tlak	Hadice - Poloměr ohybu	Položka - Hmotnost - Vnitřní
10920102	3.35 mm	1/8"	6.27 mm	22.5 MPa	40 mm	1.01 kg
10920103	4.83 mm	3/16"	7.87 mm	19 MPa	50 mm	1.31 kg
10920104	6.48 mm	1/4"	9.27 mm	18 MPa	75 mm	0.12 kg
10920105	8 mm	5/16"	11.18 mm	17.5 MPa	100 mm	0.16 kg
10920106	9.65 mm	3/8"	12.45 mm	16.5 MPa	125 mm	0.17 kg
10920108	12.83 mm	1/2"	16 mm	12 MPa	165 mm	0.23 kg
10920110	16 mm	5/8"	19.3 mm	8.8 MPa	200 mm	0.32 kg
10920112	19.18 mm	3/4"	22.86 mm	7 MPa	230 mm	0.4 kg
10920116	25.53 mm	1"	29.46 mm	6 MPa	300 mm	0.53 kg