



1096-11

P.T.F.E. ANTISTATIC



SPECIFICATIONS

Tube	PTFE	Temp max	205 °C
Safety factor	1:4	Temp min	-40 °C

DESCRIPTION

Introducing the P.T.F.E. Antistatic Hydraulic Hose, designed for exceptional performance in extreme conditions. With a working temperature range from -40°C to 205°C, this hose ensures reliability in diverse environments. Constructed from high-quality PTFE, it features a robust safety factor of 1:4, providing peace of mind during operation. The single-pipe design enhances flexibility and ease of installation, making it an ideal choice for various hydraulic applications.

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight
10961106	10 mm	3/8"	15.5 mm	12.5 MPa	50 mm	0.25 kg
10961108	13.2 mm	1/2"	18.7 mm	10.5 MPa	65 mm	0.31 kg
10961110	16 mm	5/8"	22 mm	10 MPa	80 mm	0.42 kg
10961112	19.5 mm	3/4"	26.9 mm	9 MPa	100 mm	0.56 kg
10961116	25.45 mm	1"	32.9 mm	8 MPa	125 mm	0.7 kg
10961120	32 mm	1 1/4"	39.4 mm	6.4 MPa	150 mm	0.85 kg
10961124	38.15 mm	1 1/2"	45.9 mm	5.3 MPa	200 mm	1.01 kg
10961132	50.1 mm	2"	58.4 mm	3.5 MPa	250 mm	1.27 kg
10961140	64.5 mm	2 1/2"	75 mm	2.5 MPa	320 mm	1.96 kg
10961148	76.5 mm	3"	88 mm	2 MPa	380 mm	2.51 kg