



1101-00

EGEFLEX 1



SPECIFICATIONS

Temp max	100 °C	Color	Black
Temp min	-40 °C	Standard	EN 853 1SN

DESCRIPTION

Ozone resistant hose for applications with medium/high pressures and much external abrasion. Equivalent to EN 853 1SN (25.0-4.0 MPa). Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight
11010003	5 mm	3/16"	11.8 mm	25 MPa	90 mm	0.19 kg
11010004	6.5 mm	1/4"	13.4 mm	22.5 MPa	100 mm	0.18 kg
11010005	8 mm	5/16"	15 mm	21.5 MPa	115 mm	0.22 kg
11010006	9.5 mm	3/8"	17.4 mm	18 MPa	130 mm	0.29 kg
11010008	13 mm	1/2"	20.6 mm	16 MPa	180 mm	0.35 kg
11010010	16 mm	5/8"	23.7 mm	13 MPa	200 mm	0.42 kg
11010012	19 mm	3/4"	27.7 mm	10.5 MPa	240 mm	0.53 kg
11010016	25 mm	1"	35.6 mm	8.8 MPa	300 mm	0.83 kg
11010020	32 mm	1 1/4"	43.5 mm	6.3 MPa	420 mm	1.05 kg
11010024	38 mm	1 1/2"	50.6 mm	5 MPa	500 mm	1.42 kg
11010032	51 mm	2"	64 mm	4 MPa	630 mm	2.04 kg