



1102-00

EGEFLEX 2



СПЕЦИФИКАЦИИ

technical_standard EN 853 2SN

ОПИСАНИЕ

A hose for applications with medium to high pressures and a lot of external abrasion. Equivalent to EN 853 2SN. Approved by MSHA (flame resistant). The certificates refer to dimensions 3/1"- 1". Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
11020003	5 mm	3/16"	13.4 mm	41.5 MPa	90 mm	0.31 kg
11020004	6.5 mm	1/4"	15 mm	40 MPa	100 mm	0.32 kg
11020005	8 mm	5/16"	16.6 mm	35 MPa	115 mm	0.33 kg
11020006	9.5 mm	3/8"	19 mm	33 MPa	130 mm	0.44 kg
11020008	13 mm	1/2"	22.2 mm	27.5 MPa	180 mm	0.52 kg
11020010	16 mm	5/8"	25.4 mm	25 MPa	200 mm	0.65 kg
11020012	19 mm	3/4"	29.3 mm	21.5 MPa	240 mm	0.82 kg
11020016	25 mm	1"	38.1 mm	16.5 MPa	300 mm	1.23 kg
11020020	32 mm	1 1/4"	48.3 mm	12.5 MPa	420 mm	1.79 kg
11020024	38 mm	1 1/2"	54.6 mm	9 MPa	500 mm	2.13 kg
11020032	51 mm	2"	67 mm	7.8 MPa	630 mm	2.73 kg
11020040	63 mm	2 1/2"	73.3 mm	6.9 MPa	762 mm	3.81 kg
11020048	76.2 mm	3"	91.3 mm	5 MPa	900 mm	4.17 kg