



1102-14

EGEFLEX 2 CO



SPECIFICATIONS

Safety factor	1:4	Color	Black
Temp max	100 °C	Label	Orange
Temp min	-40 °C	Standard	EN 853 2SN
Design	Wrapped		

DESCRIPTION

This hose is well suited when high pressures are required. The external polymer rubber has low friction and extra abrasion resistance. Working pressure exceeds or is equivalent to EN 853 2SN (8,0-12,5MPa).

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight	Sales - Quantity increment
11021404	6.5 mm	1/4"	15 mm	40 MPa	100 mm	0.31 kg	
1102140430	6.5 mm	1/4"	15 mm	40 MPa	100 mm	0.31 kg	210
11021405	8 mm	5/16"	16.6 mm	35 MPa	115 mm	0.34 kg	
1102140530	8 mm	5/16"	16.6 mm	35 MPa	115 mm	0.39 kg	175
11021406	10 mm	3/8"	19 mm	33 MPa	130 mm	0.45 kg	
1102140630	10 mm	3/8"	19 mm	33 MPa	130 mm	0.45 kg	135
11021408	13 mm	1/2"	22.2 mm	27.5 MPa	180 mm	0.53 kg	
1102140830	13 mm	1/2"	22.2 mm	27.5 MPa	180 mm	0.53 kg	95
11021410	16 mm	5/8"	25.4 mm	25 MPa	200 mm	0.66 kg	
11021412	19 mm	3/4"	29.3 mm	21.5 MPa	240 mm	0.83 kg	
11021416	25 mm	1"	38.1 mm	16.5 MPa	300 mm	1.24 kg	
11021420	32 mm	1 1/4"	46.7 mm	12.5 MPa	420 mm	1.82 kg	
11021424	38 mm	1 1/2"	54.5 mm	9 MPa	500 mm	2.18 kg	
11021432	51 mm	2"	66.07 mm	8 MPa	630 mm	2.81 kg	