



1103-03

KAPPAFLEX 1



SPECIFICATIONS

Color	Black	Standard	EN 857 1SC
-------	-------	----------	------------

DESCRIPTION

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 1SC. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight
11030304	6.5 mm	1/4"	11.8 mm	29 MPa	40 mm	0.18 kg
11030305	8 mm	5/16"	13.6 mm	25 MPa	55 mm	0.2 kg
11030306	9.5 mm	3/8"	16.5 mm	23 MPa	65 mm	0.24 kg
11030308	13 mm	1/2"	19 mm	20 MPa	80 mm	0.34 kg
11030310	16 mm	5/8"	22.3 mm	15 MPa	105 mm	0.4 kg
11030312	19 mm	3/4"	26.2 mm	12.5 MPa	120 mm	0.49 kg
11030316	25 mm	1"	34 mm	11 MPa	160 mm	0.71 kg
11030320	32 mm	1 1/4"	44 mm	10 MPa	300 mm	1.28 kg
11100308	13 mm	1/2"	18 mm	10 MPa	50 mm	0.27 kg