



# 1104-17

## KAPPAFLEX 2 CO SMOOTH



**LABEL.SPECIFICATIONS**

**technical\_standard** EN 857 2SC

**LABEL.DESRIPTION**

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.

| SKU      | hose_diameter_i<br>nner | hose_dimen<br>sion | hose_diameter_o<br>uter | technical_workingpr<br>essure | hose_bendra<br>dius | article_weight_int<br>ernal |
|----------|-------------------------|--------------------|-------------------------|-------------------------------|---------------------|-----------------------------|
| 11041704 | 6.5 mm                  | 1/4"               | 13.4 mm                 | 42.5 MPa                      | 75 mm               | 0.29 kg                     |
| 11041705 | 8 mm                    | 5/16"              | 15 mm                   | 40 MPa                        | 85 mm               | 0.35 kg                     |
| 11041706 | 10 mm                   | 3/8"               | 17.2 mm                 | 35 MPa                        | 90 mm               | 0.43 kg                     |
| 11041708 | 13 mm                   | 1/2"               | 20.4 mm                 | 31 MPa                        | 130 mm              | 0.58 kg                     |
| 11041710 | 16 mm                   | 5/8"               | 23.9 mm                 | 28 MPa                        | 160 mm              | 0.69 kg                     |
| 11041712 | 19 mm                   | 3/4"               | 27.7 mm                 | 28 MPa                        | 195 mm              | 0.82 kg                     |
| 11041716 | 25 mm                   | 1"                 | 35.4 mm                 | 21 MPa                        | 250 mm              | 1.18 kg                     |