



1104-17

KAPPAFLEX 2 CO SMOOTH



СПЕЦИФИКАЦИИ

technical_standard EN 857 2SC

ОПИСАНИЕ

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
11041704	6.5 mm	1/4"	13.4 mm	42.5 MPa	75 mm	0.29 kg
11041705	8 mm	5/16"	15 mm	40 MPa	85 mm	0.35 kg
11041706	10 mm	3/8"	17.2 mm	35 MPa	90 mm	0.43 kg
11041708	13 mm	1/2"	20.4 mm	31 MPa	130 mm	0.58 kg
11041710	16 mm	5/8"	23.9 mm	28 MPa	160 mm	0.69 kg
11041712	19 mm	3/4"	27.7 mm	28 MPa	195 mm	0.82 kg
11041716	25 mm	1"	35.4 mm	21 MPa	250 mm	1.18 kg