



1105-10

KAPPAFLEX 2K CO



СПЕЦИФИКАЦИИ

hose_material_reinforcement	Stålwire	technical_workingtemperature_min	-40 °C
technical_workingtemperature_max	100 °C		

ОПИСАНИЕ

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
11051004	6.5 mm	1/4"	13.4 mm	45 MPa	45 mm	0.28 kg
11051005	8 mm	5/16"	15 mm	42 MPa	60 mm	0.34 kg
11051006	10 mm	3/8"	17.4 mm	38.5 MPa	70 mm	0.37 kg
11051008	13 mm	1/2"	20.6 mm	34.5 MPa	90 mm	0.54 kg
11051010	16 mm	5/8"	23.7 mm	29 MPa	130 mm	0.66 kg
11051016	25 mm	1"	35.6 mm	20 MPa	210 mm	1.18 kg