



1105-62

KAPPAFLEX 2K CO ROCK



SPECIFICATIONS

Safety factor	1:4	Color	Black
Temp max	100 °C	Label	Green
Temp min	-40 °C	Standard	EN 857 2SC
Design	Wrapped		

DESCRIPTION

The hose is well suited for the most extreme and critical applications within, forestry, mining and construction work. A compact hose for applications with high pressures and high ozone and abrasion resistance. Exceeds EN 857 2SC. MSHA approved.

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight	Length, max
11056204	6.5 mm	1/4"	13.1 mm	45 MPa	45 mm	0.29 kg	
1105620430	6.5 mm	1/4"	13.1 mm	45 MPa	45 mm	0.29 kg	250
11056205	8 mm	5/16"	15 mm	42 MPa	60 mm	0.32 kg	
1105620530	8 mm	5/16"	15 mm	42 MPa	60 mm	0.32 kg	200
11056206	10 mm	3/8"	17.1 mm	38.5 MPa	70 mm	0.43 kg	
1105620630	10 mm	3/8"	17.1 mm	38.5 MPa	70 mm	0.43 kg	140
11056208	13 mm	1/2"	20.3 mm	34.5 MPa	90 mm	0.55 kg	
1105620830	13 mm	1/2"	20.3 mm	34.5 MPa	90 mm	0.55 kg	100
11056210	16 mm	5/8"	23.7 mm	29 MPa	130 mm	0.65 kg	
1105621030	16 mm	5/8"	23.7 mm	29 MPa	130 mm	0.65 kg	130
11056212	19 mm	3/4"	27.7 mm	28 MPa	160 mm	0.83 kg	
1105621230	19 mm	3/4"	27.7 mm	28 MPa	160 mm	0.83 kg	95
11056216	25 mm	1"	35.6 mm	20 MPa	210 mm	1.2 kg	

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight	Length, max
1105621630	25 mm	1"	35.6 mm	20 MPa	210 mm	1.2 kg	60