



1105-63

KAPPAFLEX 2K CO ROCK



SPECIFICATIONS

Tube	NBR	Temp min	-50 °C
Cover	Synthetic rubber	Design	Wrapped
Reinforcement	Steel wire	Color	Black
Safety factor	1:4	Label	Green Black text
Temp max	100 °C	Standard	EN 857 2SC

DESCRIPTION

This hose is suitable for the most extreme and critical applications within, forestry, mining and construction work. A compact hose for applications with high pressures and high ozon and abrasion resistance, Exceeds EN 857 2SC and ISO 18752-AS. Impulse tested 1 000 000 cycles. (1.1/4" to 200 000 cycles).

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight	Sales - Quantity increment	Length, min	Length, max
11056304	6.5 mm	1/4"	13.4 mm	45 MPa	45 mm	0.27 kg			
1105630430	6.5 mm	1/4"	13.4 mm	45 MPa	45 mm	0.27 kg	230	170	230
11056305	8 mm	5/16"	15 mm	42 MPa	60 mm	0.32 kg			
1105630530	8 mm	5/16"	15 mm	42 MPa	60 mm	0.32 kg	190	130	190
11056306	10 mm	3/8"	17.4 mm	38.5 MPa	70 mm	0.37 kg			
1105630630	10 mm	3/8"	17.4 mm	38.5 MPa	70 mm	0.37 kg	160	110	160
11056308	13 mm	1/2"	20.6 mm	35 MPa	90 mm	0.51 kg			
1105630830	13 mm	1/2"	20.6 mm	35 MPa	90 mm	0.51 kg	110	75	110
11056310	16 mm	5/8"	23.6 mm	29 MPa	130 mm	0.66 kg			
11056312	19 mm	3/4"	27.7 mm	28 MPa	160 mm	0.85 kg			
1105631230	19 mm	3/4"	27.7 mm	28 MPa	160 mm	0.85 kg	135	105	135
11056316	25 mm	1"	35.6 mm	20 MPa	210 mm	1.13 kg			
11056320	32 mm	1 1/4"	43.5 mm	17.5 MPa	300 mm	1.56 kg			