



1115-02

GAMMAFLEX 4



СПЕЦИФИКАЦИИ

hose_material_inner	Syntetisk gummi	technical_workingtemperature_max	100 °C
hose_material_cover	Syntetisk gummi	technical_workingtemperature_min	-40 °C
hose_material_reinforcement	Stålspiral	technical_standard	EN 856 4SP

ОПИСАНИЕ

The hose is suitable for high pressures combined with high flexing. The hose is equivalent to EN856 4SP and MSHA-approved (Flame resistant).

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
11150204	6.5 mm	1/4"	17.4 mm	45 MPa	150 mm	0.57 kg
11150206	10 mm	3/8"	21.2 mm	44.5 MPa	180 mm	0.72 kg
11150208	13 mm	1/2"	24.4 mm	41.5 MPa	230 mm	0.86 kg
11150210	16 mm	5/8"	28 mm	35 MPa	250 mm	1.03 kg
11150212	19 mm	3/4"	32 mm	35 MPa	300 mm	1.48 kg
11150216	25 mm	1"	39 mm	28 MPa	340 mm	1.87 kg
11150224	38 mm	1 1/2"	56.4 mm	18.5 MPa	560 mm	3.5 kg