



# 1115-10

## DELTAFLX 4 CT



### SPECIFICATIONS

<b>Hose - Inner tube material</b>	NBR	<b>Technical - Working Temperature Min</b>	-40 °C
<b>Hose - Top cover material</b>	Synthetic rubber	<b>Technical - Color</b>	Black
<b>Hose - Reinforcement materials</b>	Steel spiral	<b>Technical - Standard</b>	EN 856 4SP
<b>Technical - Working Temperature Max</b>	121 °C		

### DESCRIPTION

Flexible hydraulic hose for high pressures in combination with very high pulsations. Equivalent to EN 856 4SP/4SH (1 1/4"-2"). Fire resistant (MSHA approved). The hose has a very durable cover. Ferrule: 4200-19-xx (use only with 3/8"-1", no skive), 4200-20-xx (us only with 1 1/4"-2", no skive), 4700-04-xx (use only with 3/4"-2", no skive), 4700-09-xx (use only with 3/4"-2", outer skive), 4200-25-xx (use only with 3/6"-1" no skive)

SKU	Hose - Inner diameter	Hose - Dimension	Hose - Outer diameter	Technical - Working pressure	Hose - Bend radius	Article - Weight - Internal	Technical - Color
11151006	10 mm	3/8"	21.4 mm	44.5 MPa	130 mm	0.7 kg	Black
11151008	13 mm	1/2"	24.6 mm	42.5 MPa	180 mm	0.85 kg	Black
11151010	16 mm	5/8"	28.2 mm	39 MPa	225 mm	1.13 kg	Black
11151012	19 mm	3/4"	32.2 mm	35 MPa	280 mm	1.41 kg	Black
11151016	25 mm	1"	39.7 mm	32 MPa	340 mm	1.85 kg	Black
11151020	32 mm	1 1/4"	45.5 mm	34.5 MPa	460 mm	2.57 kg	Black
11151024	38 mm	1 1/2"	53.5 mm	29 MPa	560 mm	3.32 kg	Black
11151032	51 mm	2"	68.1 mm	25 MPa	700 mm	4.5 kg	Black