



1115-10

DELTAFLX 4 CT



SPECIFICATIONS

Tube	NBR	Temp min	-40 °C
Cover	Synthetic rubber	Color	Black
Reinforcement	Steel spiral	Standard	EN 856 4SP
Temp max	121 °C		

DESCRIPTION

Flexible hydraulic hose for high pressures in combination with high pulsations. The external polymer rubber has low friction and extra abrasion resistance. Working pressure is equivalent to, or exceeds, EN 856 4SP

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight	Color
11151006	10 mm	3/8"	21.4 mm	44.5 MPa	130 mm	0.7 kg	Black
11151008	13 mm	1/2"	24.6 mm	42.5 MPa	180 mm	0.85 kg	Black
11151010	16 mm	5/8"	28.2 mm	39 MPa	225 mm	1.13 kg	Black
11151012	19 mm	3/4"	32.2 mm	35 MPa	280 mm	1.41 kg	Black
11151016	25 mm	1"	39.7 mm	32 MPa	340 mm	1.85 kg	Black
11151020	32 mm	1 1/4"	45.5 mm	34.5 MPa	460 mm	2.57 kg	Black
11151024	38 mm	1 1/2"	53.5 mm	29 MPa	560 mm	3.32 kg	Black
11151032	51 mm	2"	68.1 mm	25 MPa	700 mm	4.5 kg	Black