



1115-10

DELTAFLEX 4 CT



LABEL.SPECIFICATIONS

hose_material_inner	NBR	technical_workingtemperature_max	121 °C
hose_material_cover	Synteettinen kumi	technical_workingtemperature_min	-40 °C
hose_material_reinforcement	Terässpiraali	technical_standard	EN 856 4SP

LABEL.DESRIPTION

Flexible hydraulic hose for high pressures in combination with high pulsations. The external polymer rubber has low friction and extra abrasion resistance. Working pressure is equivalent to, or exceeds, EN 856 4SP

SKU	hose_diameter_i nner	hose_dimen sion	hose_diameter_o uter	technical_workingpr essure	hose_bendra dius	article_weight_int ernal
11151006	10 mm	3/8"	21.4 mm	44.5 MPa	130 mm	0.7 kg
11151008	13 mm	1/2"	24.6 mm	42.5 MPa	180 mm	0.85 kg
11151010	16 mm	5/8"	28.2 mm	39 MPa	225 mm	1.13 kg
11151012	19 mm	3/4"	32.2 mm	35 MPa	280 mm	1.41 kg
11151016	25 mm	1"	39.7 mm	32 MPa	340 mm	1.85 kg
11151020	32 mm	1 1/4"	45.5 mm	34.5 MPa	460 mm	2.57 kg
11151024	38 mm	1 1/2"	53.5 mm	29 MPa	560 mm	3.32 kg
11151032	51 mm	2"	68.1 mm	25 MPa	700 mm	4.5 kg