



1115-10

DELTAFLEX 4 CT



LABEL.SPECIFICATIONS

hose_material_inner	NBR	technical_workingtemperature_max	121 °C
hose_material_cover	Synthetic rubber	technical_workingtemperature_min	-40 °C
hose_material_reinforcement	Steel spiral	technical_standard	EN 856 4SP

LABEL.DESRIPTION

Elastīga hidrauliskā šļūtene augstam spiedienam kombinācijā ar ļoti lielām pulsācijām. Atbilst EN 856 4SP / 4SH (1 1/4" - 2" "). Ugunsizturīga (apstiprināta MSHA).

SKU	hose_diameter_i nner	hose_dimen sion	hose_diameter_o uter	technical_workingpr essure	hose_bendra dius	article_weight_int ernal
11151006	10 mm	3/8"	21.4 mm	44.5 MPa	130 mm	0.7 kg
11151008	13 mm	1/2"	24.6 mm	42.5 MPa	180 mm	0.85 kg
11151010	16 mm	5/8"	28.2 mm	39 MPa	225 mm	1.13 kg
11151012	19 mm	3/4"	32.2 mm	35 MPa	280 mm	1.41 kg
11151016	25 mm	1"	39.7 mm	32 MPa	340 mm	1.85 kg
11151020	32 mm	1 1/4"	45.5 mm	34.5 MPa	460 mm	2.57 kg
11151024	38 mm	1 1/2"	53.5 mm	29 MPa	560 mm	3.32 kg
11151032	51 mm	2"	68.1 mm	25 MPa	700 mm	4.5 kg