



1115-10

DELTAFLEX 4 CT



СПЕЦИФИКАЦИИ

hose_material_inner	NBR	technical_workingtemperature_max	121 °C
hose_material_cover	Syntetisk gummi	technical_workingtemperature_min	-40 °C
hose_material_reinforcement	Stålspiral	technical_standard	EN 856 4SP

ОПИСАНИЕ

Flexible hydraulic hose for high pressures in combination with high pulsations. The external polymer rubber has low friction and extra abrasion resistance. Working pressure is equivalent to, or exceeds, EN 856 4SP

SKU	hose_diameter_inner	hose_dimension	hose_diameter_outer	technical_workingpressure	hose_bendradius	article_weight_internal
11151006	10 mm	3/8"	21.4 mm	44.5 MPa	130 mm	0.7 kg
11151008	13 mm	1/2"	24.6 mm	42.5 MPa	180 mm	0.85 kg
11151010	16 mm	5/8"	28.2 mm	39 MPa	225 mm	1.13 kg
11151012	19 mm	3/4"	32.2 mm	35 MPa	280 mm	1.41 kg
11151016	25 mm	1"	39.7 mm	32 MPa	340 mm	1.85 kg
11151020	32 mm	1 1/4"	45.5 mm	34.5 MPa	460 mm	2.57 kg
11151024	38 mm	1 1/2"	53.5 mm	29 MPa	560 mm	3.32 kg
11151032	51 mm	2"	68.1 mm	25 MPa	700 mm	4.5 kg