



1135-85



SPECIFICATIONS

| | | | |
|-------------------------------------|------------------|-------------------------------------|--------------|
| Hose - Inner tube material | Synthetic rubber | Technical - Working Temperature Min | -40 °C |
| Hose - Top cover material | Synthetic rubber | Technical - Color | Black |
| Hose - Reinforcement materials | Steel spiral | Technical - Standard | ISO 18752 CC |
| Technical - Working Temperature Max | 120 °C | | |

DESCRIPTION

A very flexible spiral hose for the toughest applications. With the extremely durable cover and flexibility, the hose is suited for applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of ISO 18752 CC.

| SKU | Hose - Inner diameter | Hose - Dimension | Hose - Outer diameter | Technical - Working pressure | Hose - Bend radius | Article - Weight - Internal | Technical - Color |
|----------|-----------------------|------------------|-----------------------|------------------------------|--------------------|-----------------------------|-------------------|
| 11358508 | 13 mm | 1/2" | 22.8 mm | 35 MPa | 90 mm | 0.75 kg | Black |
| 11358510 | 16 mm | 5/8" | 26.5 mm | 35 MPa | 105 mm | 1.08 kg | Black |
| 11358512 | 19 mm | 3/4" | 29.8 mm | 35 MPa | 125 mm | 1.18 kg | Black |
| 11358516 | 25 mm | 1" | 37.1 mm | 35 MPa | 150 mm | 1.71 kg | Black |
| 11358520 | 32 mm | 1 1/4" | 44.5 mm | 35 MPa | 210 mm | 2.47 kg | Black |