



1201-10

SPIR STAR TYPE 2



SPECIFICATIONS

Tube	PA	Temp max	60 °C
Cover	PA	Temp min	-30 °C
Reinforcement	Steel spiral	Design	Smooth
Safety factor	1:2.5	Color	Green

DESCRIPTION

The SPIR STAR TYPE 2 is a green hydraulic hose designed for reliable performance with oil and water media. It features a single pipe construction with a PA inner tube and smooth PA top cover, reinforced by a steel spiral for enhanced durability. Engineered to operate safely within temperatures from -30°C to 60°C, it offers a safety factor of 1:2.5, ensuring robust and secure hydraulic applications.

SKU	ID	Size	OD	Wp	Bend radii [mm]	Weight
12011002	4 mm	1/8"	8 mm	120 MPa	75 mm	0.11 kg
12011003	5 mm	3/16"	9.4 mm	104 MPa	95 mm	0.13 kg
12011004	6 mm	1/4"	11.5 mm	100 MPa	110 mm	0.18 kg
12011005	8 mm	5/16"	13.3 mm	90 MPa	130 mm	0.2 kg
12011006	10 mm	3/8"	15.5 mm	69 MPa	160 mm	0.28 kg
12011008	13 mm	1/2"	19.3 mm	69 MPa	200 mm	0.44 kg
12011012	19 mm	3/4"	26.2 mm	52 MPa	240 mm	0.75 kg