



1401-00

HYDROWATER, INDUSTRIAL WATER HOSE 12 BAR



SPECIFICATIONS

Cover	SBR/EPDM	Media	Water
Tube	Synthetic rubber SBR	Safety factor	1:3
Reinforcement	Textile	Temp min	-30 °C
Resistance cover	Abrasion, Weather	Temp max	80 °C
Design	Smooth	Color	Red

DESCRIPTION

Flush hose for industries, construction sites, sports facilities and wash halls. Easy to handle, low weight, durable and weather resistant. 13-25mm extruded smooth cover and 32-152mm with wrapped cover

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14010008	13 mm	19 mm	1.2 MPa	80 mm	50 m	0.25 kg
14010010	16 mm	23 mm	1.2 MPa	100 mm	50 m	0.36 kg
14010012	19 mm	26 mm	1.2 MPa	110 mm	50 m	0.47 kg
14010016	25 mm	33 mm	1.2 MPa	150 mm	50 m	0.68 kg
14010020	32 mm	42 mm	1 MPa	192 mm	40 m	0.9 kg
14010024	38 mm	48 mm	1 MPa	228 mm	40 m	1.02 kg
14010025	45 mm	55 mm	1 MPa	271 mm	40 m	1.26 kg
14010032	50 mm	60 mm	1 MPa	300 mm	40 m	1.22 kg
14010040	63 mm	73 mm	1 MPa	381 mm	40 m	1.56 kg
14010048	75 mm	86 mm	1 MPa	450 mm	40 m	1.91 kg
14010064	102 mm	114 mm	1 MPa	800 mm	40 m	3.21 kg
14010096	152 mm	162 mm	1 MPa	1220 mm	40 m	5.2 kg