



1402-00

INDUSTRIAL COOLING HOSE, FIBERGLASS



SPECIFICATIONS

Cover	EPDM	Media	Water
Tube	EPDM	Safety factor	1:3
Reinforcement	Textile	Temp min	-30 °C
Resistance cover	Heat	Temp max	120 °C
Design	Textile	Color	White

DESCRIPTION

Used as a protection and cooling hose where the working temperature is high, e.g. melting furnaces and foundries. The cover cord is made of fiberglass, which gives the hose a good resistance towards flames. Sustains 530° C temporary radiation as well as glowing steel spatter.

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14020008	13 mm	29 mm	1.2 MPa	50 mm	40 m	0.44 kg
14020010	16 mm	32 mm	1.2 MPa	85 mm	40 m	0.77 kg
14020012	19 mm	35 mm	1.2 MPa	95 mm	40 m	0.69 kg
14020016	25 mm	41 mm	1.2 MPa	125 mm	40 m	0.73 kg
14020020	32 mm	48 mm	1.2 MPa	160 mm	40 m	0.88 kg
14020024	38 mm	55 mm	1.2 MPa	380 mm	40 m	1.1 kg
14020026	40 mm	57 mm	1.2 MPa	400 mm	40 m	1.9 kg
14020030	45 mm	63 mm	1.2 MPa	450 mm	40 m	2.1 kg
14020032	51 mm	71 mm	1.2 MPa	250 mm	40 m	2.24 kg
14020040	63.5 mm	81 mm	1.2 MPa	630 mm	40 m	2.91 kg
14020048	76 mm	96 mm	1.2 MPa	380 mm	40 m	3.3 kg