



1409-85

MULTIHEAT S/D 10 BAR



SPECIFICATIONS

Cover	EPDM	Media	Water
Tube	EPDM	Safety factor	1:3
Reinforcement	Steel wire, Textile	Temp min	-40 °C
Resistance cover	Heat, weather	Temp max	125 °C
Design	Wrapped	Color	Black

DESCRIPTION

Very flexible hose. Used as a hot water hose in the industry. Resistance to diluted chemicals. AdBlue resistant.

SKU	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
14098508	13 mm	21 mm	1 MPa	92	50 mm	40 m	0.32 kg
14098510	16 mm	24 mm	1 MPa	92	60 mm	40 m	0.41 kg
14098512	19 mm	28 mm	1 MPa	92	70 mm	40 m	0.51 kg
14098514	22 mm	33 mm	1 MPa	92	85 mm	40 m	0.6 kg
14098516	25 mm	34 mm	1 MPa	92	95 mm	40 m	0.61 kg
14098518	28 mm	38 mm	1 MPa	92	110 mm	40 m	0.79 kg
14098520	32 mm	42 mm	1 MPa	92	125 mm	40 m	0.96 kg
14098522	35 mm	46 mm	1 MPa	92	135 mm	40 m	1.06 kg
14098524	38 mm	48 mm	1 MPa	92	150 mm	40 m	1.13 kg
14098530	45 mm	57 mm	1 MPa	92	160 mm	40 m	1.49 kg
14098532	51 mm	62 mm	1 MPa	92	215 mm	40 m	1.69 kg
14098540	63 mm	76 mm	1 MPa	92	280 mm	40 m	2.02 kg
14098548	76 mm	89 mm	1 MPa	92	350 mm	40 m	2.76 kg
14098564	102 mm	116 mm	1 MPa	92	490 mm	40 m	4.16 kg

SKU	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
14098580	127 mm	142 mm	1 MPa	92	620 mm	40 m	5.27 kg
14098596	152 mm	174 mm	1 MPa	92	950 mm	40 m	9.28 kg