



1415-2x

SEWER FLUSH HOSE 250 BAR



SPECIFICATIONS

Cover	NR/CR	Media	Water
Tube	Synthetic rubber SBR	Safety factor	1:2.5
Reinforcement	Textile	Temp min	-35 °C
Resistance cover	Abrasion, Weather	Temp max	80 °C
Design	Smooth	Color	Black

DESCRIPTION

Hose for high pressure flushing of sewers and sewage systems. Its abrasion proof cover and textile reinforcement make it flexible and very easy to handle. Supplied pre-assembled with BSP couplings and pressure test certificate. Coupling: 1415-91-xx, 1415-92-xx

SKU	ID	OD	Wp	Bend radii [mm]	Lengt h	Weight	Type 1	Thread type 1	Size 1	Type 1	Type 2	Thread type 2	Size 2	Type 2
14152016	25 mm	39.3 mm	25 MPa	100 mm	200 m	173 kg	Thread	G	1"	Female	Thread	G	1"	Male
14152408	13 mm	25 mm	25 MPa	70 mm	80 m	36.8 kg	Thread	G	1/2"	Female	Thread	G	1/2"	Male
14152508	13 mm	25 mm	25 MPa	70 mm	120 m	55.2 kg	Thread	G	1/2"	Female	Thread	G	1/2"	Male
14152516	25 mm	39 mm	25 MPa	110 mm	120 m	103.92 kg	Thread	G	1"	Female	Thread	G	1"	Male
14153016	25 mm	39 mm	25 MPa	110 mm	150 m	129.9 kg	Thread	G	1"	Female	Thread	G	1"	Male