



1415-xx90

AQUASEWER, FLUSHING HOSE 250 BAR, BSP MALE - BSP MALE



SPECIFICATIONS

| | | | |
|-------------------------|----------------------|----------------------|--------|
| Cover | NR/BR | Media | Water |
| Tube | Synthetic rubber SBR | Safety factor | 1:2.5 |
| Reinforcement | Textile | Temp min | -35 °C |
| Resistance cover | Abrasion, Weather | Temp max | 80 °C |
| Design | Smooth | Color | Black |

DESCRIPTION

Hose for high pressure flushing of sewers and sewage systems. Its abrasion proof cover and textile reinforcement make it flexible and very easy to handle. Supplied pre-assembled with BSP couplings and pressure test certificate. Coupling: 1415-91-xx, 1415-92-xx

| SKU | ID | OD | Wp | Bend radii [mm] | Lengt h | Weight | Type 1 | Thread type 1 | Size 1 | Type 1 | Type 2 | Thread type 2 | Size 2 | Type 2 |
|------------|-------|-------|--------|--------------------|------------|-----------|-----------|------------------|-----------|-----------|-----------|------------------|-----------|-----------|
| 1415060890 | 13 mm | 25 mm | 25 MPa | 70 mm | 60 m | 27.6 kg | Thread | G | 1/2" | Male | Thread | G | 1/2" | Male |
| 1415080890 | 13 mm | 25 mm | 25 MPa | 70 mm | 80 m | 36.8 kg | Thread | G | 1/2" | Male | Thread | G | 1/2" | Male |
| 1415120890 | 13 mm | 25 mm | 25 MPa | 70 mm | 120 m | 55.25 kg | Thread | G | 1/2" | Male | Thread | G | 1/2" | Male |
| 1415121690 | 25 mm | 39 mm | 25 MPa | 110 mm | 120 m | 103.92 kg | Thread | G | 1" | Male | Thread | G | 1" | Male |
| 1415151690 | 25 mm | 39 mm | 25 MPa | 110 mm | 150 m | 129.9 kg | Thread | G | 1" | Male | Thread | G | 1" | Male |
| 1415161690 | 25 mm | 39 mm | 25 MPa | 110 mm | 160 m | 138.5 kg | Thread | G | 1" | Male | Thread | G | 1" | Male |