



1415-xx

AQUASEWER, FLUSHING HOSE 250 BAR, BSP FEMALE - BSP MALE



SPECIFICATIONS

Cover	NR/BR	Media	Water
Tube	Synthetic rubber SBR	Safety factor	1:2.5
Reinforcement	Textile	Temp min	-35 °C
Resistance cover	Abrasion, Weather	Temp max	80 °C
Design	Smooth	Color	Black

DESCRIPTION

Hose for high pressure flushing of sewers and sewage systems. Its abrasion proof cover and textile reinforcement make it flexible and very easy to handle. Supplied pre-assembled with BSP couplings and pressure test certificate. Coupling: 1415-91-xx, 1415-92-xx

SKU	ID	OD	Wp	Bend radii [mm]	Lengt h	Weight	Type 1	Thread type 1	Size 1	Type 1	Type 2	Thread type 2	Size 2	Type 2
14150608	13 mm	25 mm	25 MPa	70 mm	60 m	27.6 kg	Thread	G	1/2"	Female	Thread	G	1/2"	Male
14150808	13 mm	25 mm	25 MPa	70 mm	80 m	36.8 kg	Thread	G	1/2"	Female	Thread	G	1/2"	Male
14150812	19 mm	31.6 mm	25 MPa	90 mm	80 m	48.8 kg	Thread	G	3/4"	Female	Thread	G	3/4"	Male
14151208	13 mm	25 mm	25 MPa	70 mm	120 m	87 kg	Thread	G	1/2"	Female	Thread	G	1/2"	Male
14151212	19 mm	31.6 mm	25 MPa	90 mm	120 m	73.2 kg	Thread	G	3/4"	Female	Thread	G	3/4"	Male
14151216	25 mm	39 mm	25 MPa	110 mm	120 m	103.92 kg	Thread	G	1"	Female	Thread	G	1"	Male
14151220	32 mm	48 mm	25 MPa	150 mm	120 m	153.84 kg	Thread	G	1 1/4"	Female	Thread	G	1 1/4"	Male
14151516	25 mm	39 mm	25 MPa	110 mm	150 m	129.9 kg	Thread	G	1"	Female	Thread	G	1"	Male
14151520	32 mm	48 mm	25 MPa	150 mm	150 m	192.3 kg	Thread	G	1 1/4"	Female	Thread	G	1 1/4"	Male
14151820	32 mm	48 mm	25 MPa	150 mm	180 m	230 kg	Thread	G	1 1/4"	Female	Thread	G	1 1/4"	Male