




1420-00

HYDROAIR, AIR PRESSURE HOSE, 15 BAR



SPECIFICATIONS

Cover	SBR	Media	Air, Air pressure
Tube	SBR	Safety factor	1:3
Reinforcement	Textile	Temp min	-25 °C
Resistance cover	Abrasion, Weather	Temp max	70 °C
Design	Smooth	Color	Black

DESCRIPTION

Air pressure hose for most applications, tools, air pressure units and rock drills etc. Used in engineering, mining and construction industries. Sustains oil mist. 6-25mm extruded smooth cover and 32-102mm with wrapped cover

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14200004	6 mm	12 mm	1.5 MPa	50 mm	40 m	0.13 kg
14200005	8 mm	14 mm	1.5 MPa	65 mm	40 m	0.16 kg
14200006	10 mm	17 mm	1.5 MPa	80 mm	40 m	0.23 kg
14200008	13 mm	22 mm	1.5 MPa	105 mm	40 m	0.38 kg
14200010	16 mm	25 mm	1.5 MPa	130 mm	40 m	0.44 kg
14200012	19 mm	28 mm	1.5 MPa	150 mm	40 m	0.51 kg
14200016	25 mm	36 mm	1.5 MPa	200 mm	40 m	0.8 kg
14200020	32 mm	44 mm	1.5 MPa	320 mm	40 m	1.03 kg
14200024	38 mm	52 mm	1.5 MPa	380 mm	40 m	1.36 kg
14200032	51 mm	65 mm	1.5 MPa	500 mm	40 m	1.86 kg
14200040	63 mm	78 mm	1.5 MPa	650 mm	40 m	2.24 kg
14200048	76 mm	90 mm	1.5 MPa	750 mm	40 m	2.46 kg
14200064	102 mm	115 mm	1.5 MPa	1000 mm	40 m	3.25 kg