



# 1425-75

## DRAGMAN STANDARD



### SPECIFICATIONS

|                         |                   |                      |                                |
|-------------------------|-------------------|----------------------|--------------------------------|
| <b>Cover</b>            | PU                | <b>Media</b>         | Air pressure, Water, Materials |
| <b>Tube</b>             | PU                | <b>Safety factor</b> | 1:4                            |
| <b>Reinforcement</b>    | Textile           | <b>Temp min</b>      | -50 °C                         |
| <b>Resistance cover</b> | Abrasion, Weather | <b>Temp max</b>      | 75 °C                          |
| <b>Design</b>           | Smooth            | <b>Color</b>         | Orange                         |
| <b>Design</b>           | Flat Coil         |                      |                                |

### DESCRIPTION

Air pressure hose designed for construction sites (well drilling) where low weight is appreciated. Due to the PU-design, the hose sustains an extreme amount of external abrasion and can be stored laying flat.

| SKU      | ID     | OD       | Wp       | Coil lenght | Weight  |
|----------|--------|----------|----------|-------------|---------|
| 14257556 | 90 mm  | 96.4 mm  | 1.5 MPa  | 100 m       | 1.05 kg |
| 14257564 | 102 mm | 109.2 mm | 1.35 MPa | 100 m       | 1.35 kg |
| 14257574 | 114 mm | 121.2 mm | 1.2 MPa  | 100 m       | 1.5 kg  |
| 14257580 | 127 mm | 134.2 mm | 1 MPa    | 100 m       | 1.65 kg |
| 14257596 | 152 mm | 159.6 mm | 0.9 MPa  | 0 m         | 2.1 kg  |