



1432-30

YACHTOIL SW, MARINE FUEL HOSE, ISO 7840 4- 25 MM



SPECIFICATIONS

Cover	CR	Safety factor	1:3
Tube	NBR	Standard	ISO 7840 A1
Reinforcement	Textile	Temp min	-35 °C
Resistance cover	Abrasion, Weather	Temp max	90 °C
Design	Smooth	Color	Black
Media	Oil and gasoline		

DESCRIPTION

Very flexible fuel hose that is resistant to gasoline, unleaded gasoline and diesel. The hose is manufactured according to SS-EN ISO 7840 A1 regarding flame resistance and permeability. This means that it can sustain 2,5 minutes in open fire without leaking. For larger dimensions, see 1432-31.

SKU	ID	OD	Wp	Bend radii [mm]	Coil length	Weight
14323002	4 mm	14.5 mm	1 MPa	25 mm	50 m	0.23 kg
14323003	5 mm	12.5 mm	1 MPa	50 mm	50 m	0.15 kg
14323004	6 mm	13.5 mm	1 MPa	60 mm	50 m	0.17 kg
14323005	8 mm	16.5 mm	1 MPa	80 mm	50 m	0.24 kg
14323006	10 mm	18.5 mm	1 MPa	100 mm	50 m	0.28 kg
14323008	13 mm	22.5 mm	1 MPa	130 mm	50 m	0.4 kg
14323010	16 mm	25.5 mm	1 MPa	160 mm	50 m	0.46 kg
14323012	19 mm	29.5 mm	1 MPa	190 mm	50 m	0.59 kg
14323016	25 mm	35.8 mm	1 MPa	150 mm	50 m	0.86 kg