



1432-31

YACHTOIL SW, MARINE FUEL HOSE, ISO 7840



SPECIFICATIONS

Cover	CR	Safety factor	1:3
Tube	NBR	Standard	ISO 7840 A1
Reinforcement	Textile	Temp min	-20 °C
Resistance cover	Flames, Oil, Weather	Temp max	80 °C
Design	Wrapped	Color	Black
Media	Oil and gasoline		

DESCRIPTION

Hose manufactured according to SS-EN ISO 7840 A1 regarding flame resistance and permeability. This means that it can sustain 2,5 minutes in open fire without leaking. It is used as a fuel refill hose on smaller boats. ISO 7840 A1 E10/B10 compatible.

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14323116	25 mm	38 mm	0.5 MPa	150 mm	40 m	0.86 kg
14323120	32 mm	41 mm	0.5 MPa	160 mm	61 m	0.84 kg
14323124	38 mm	50 mm	0.5 MPa	190 mm	61 m	1.24 kg
14323132	51 mm	63 mm	0.25 MPa	250 mm	61 m	1.58 kg
14323140	63 mm	76 mm	0.25 MPa	320 mm	61 m	1.19 kg