



1432-33

YACHTOIL, MARINE FILLING HOSE ISO 7840 A1



SPECIFICATIONS

Cover	Rubber	Safety factor	1:4
Tube	NBR	Standard	ISO 7840 A1
Reinforcement	Textile and steel spiral	Temp min	-35 °C
Resistance cover	Wear, Oil, Petrol, Weather, Heat, Ozone	Temp max	80 °C
Design	Textile	Color	Black
Media	Oil, Gasoline, Special		

DESCRIPTION

Heat-resistant hose for refueling recreational boats (max. length 24m) with permanently installed internal engine. Manufactured in accordance with ISO 7840 A1 CE. Max. aromatic content 50%. ISO 7840 A1 E10/B10 compatible.

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14323312	19 mm	31 mm	0.25 MPa	90 mm	24 m	0.76 kg
14323316	25 mm	37 mm	0.25 MPa	125 mm	24 m	0.92 kg
14323320	32 mm	44 mm	0.25 MPa	160 mm	24 m	1.15 kg
14323324	38 mm	50 mm	0.25 MPa	225 mm	24 m	0.01 kg
14323332	51 mm	63 mm	0.25 MPa	254 mm	24 m	0.01 kg
14323340	60 mm	72 mm	0.25 MPa	300 mm	24 m	2.23 kg