



1432-50

MULTIOIL, OIL PRESSURE HOSE SAE J30R2 AND SAE J30R6 20 BAR



SPECIFICATIONS

Cover	Synthetic rubber	Safety factor	1:3
Tube	NBR	Standard	SAE J30 R2, SAE J30 R6
Reinforcement	Synthetic textile	Temp min	-40 °C
Resistance cover	Abrasion, Weather	Temp max	100 °C
Design	Smooth	Color	Black
Media	Oil and gasoline		

DESCRIPTION

Very good all-round hose for many applications, such as return hose for hydraulic systems, diesel, gasoline, unleaded gasoline and E85 fuels with max. content of aromatics of 60%. Used in vehicles by land and sea. Suitable for the usage in engine compartments of engine-driven vehicles. The cover is resistant to external oil, abrasion, weather and heat. Electric resistance 106 Ohm.

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14325004	6 mm	13 mm	2 MPa	36 mm	40 m	0.15 kg
14325005	8 mm	15 mm	2 MPa	48 mm	40 m	0.18 kg
14325006	10 mm	17 mm	2 MPa	60 mm	40 m	0.22 kg
14325008	13 mm	20 mm	2 MPa	80 mm	40 m	0.31 kg
14325010	16 mm	24 mm	2 MPa	100 mm	40 m	0.42 kg
14325012	20 mm	29 mm	2 MPa	120 mm	40 m	0.55 kg
14325016	25 mm	35 mm	2 MPa	150 mm	40 m	0.77 kg