



# 1432-85

## HOSE FOR BIO DIESEL (B5, B10, B20, B100) SAE30R9



### SPECIFICATIONS

<b>Cover</b>	CPE	<b>Media</b>	Oil and gasoline
<b>Tube</b>	FKM	<b>Safety factor</b>	1:9
<b>Reinforcement</b>	Polyester	<b>Temp min</b>	-34 °C
<b>Resistance cover</b>	Abrasion, Weather	<b>Temp max</b>	135 °C
<b>Design</b>	Smooth	<b>Color</b>	Black

### DESCRIPTION

Fuel hose designed for, among others, car and truck injection systems. The hose is CARB certified (Q-10-004) with a maximum fuel permeability of 15g/m<sup>2</sup>/day at +40° and certified according to EPA EVTIPLINE 110-001. The hose can be used on several types of fuel such as gasoline, ethanol extended gasoline, diesel, biodiesel (B5, B10, B20) and lubricating oil. NOTE; The hose is not suitable for lying in fuel.

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14328504	6.3 mm	12.7 mm	0.7 MPa	19 mm	25 m	0.15 kg
14328505	7.9 mm	14 mm	0.7 MPa	21 mm	25 m	0.18 kg
14328506	9.5 mm	16 mm	0.7 MPa	24 mm	25 m	0.21 kg
14328508	13 mm	20 mm	0.7 MPa	40 mm	25 m	0.24 kg