



1434-70

MARITIM HOSE FOR WET EXHAUST SAE J2006 R1 AND R2



SPECIFICATIONS

Cover	EPDM	Safety factor	1:3
Tube	EPDM	Standard	SAE J 2006 R1 & R2, ISO 13363
Reinforcement	Textile and steel spiral	Temp min	-30 °C
Resistance cover	Abrasion, Weather	Temp max	120 °C
Design	Corrugated	Color	Black
Media	Ventilation		

DESCRIPTION

Marine diesel and exhaust hose according to SAE J2006 R1, R2 and ISO 13363. Resistant to water, wet exhaust gases, ozone and UV-abrasion. Low weight with corrugated cover. The steel spiral and the design of the hose make it very flexible. Approved by Lloyds Register of Shipping.

SKU	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
14347012	19 mm	29 mm	0.4 MPa	80	40 mm	40 m	0.27 kg
14347016	25 mm	35 mm	0.4 MPa	80	45 mm	40 m	0.5 kg
14347019	30 mm	40 mm	0.4 MPa	80	45 mm	40 m	0.45 kg
14347020	32 mm	40 mm	0.4 MPa	80	48 mm	40 m	0.65 kg
14347024	40 mm	50 mm	0.4 MPa	80	60 mm	40 m	0.89 kg
14347028	45 mm	55 mm	0.4 MPa	80	68 mm	40 m	1.01 kg
14347032	51 mm	61 mm	0.4 MPa	80	78 mm	40 m	1.14 kg
14347035	57 mm	67 mm	0.3 MPa	80	86 mm	40 m	1.26 kg
14347039	60 mm	70 mm	0.3 MPa	80	90 mm	40 m	1.32 kg
14347040	65 mm	73 mm	0.3 MPa	80	95 mm	40 m	1.4 kg
14347048	76 mm	87 mm	0.3 MPa	80	115 mm	40 m	1.62 kg
14347056	90 mm	101 mm	0.2 MPa	80	135 mm	40 m	2.12 kg
14347064	102 mm	112 mm	0.2 MPa	80	155 mm	20 m	2.35 kg

SKU	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil length	Weight
14347069	110 mm	122 mm	0.2 MPa	80	167 mm	20 m	2.83 kg
14347080	127 mm	139 mm	0.2 MPa	80	190 mm	20 m	3.19 kg
14347096	152 mm	165 mm	0.2 MPa	80	230 mm	20 m	4.17 kg
14347203	203 mm	218 mm	0.2 MPa	80	305 mm	20 m	6.54 kg
14347254	254 mm	269 mm	0.2 MPa	80	450 mm	20 m	
14347302	302 mm	318 mm	0.2 MPa	80	700 mm	20 m	10.85 kg