



# 1435-00

## TANKOIL SW, GAS TRUCK HOSE 10 BAR



### SPECIFICATIONS

<b>Cover</b>	NBR/SBR	<b>Media</b>	Oil and gasoline
<b>Tube</b>	NBR	<b>Safety factor</b>	1:3
<b>Reinforcement</b>	Textile	<b>Temp min</b>	-35 °C
<b>Resistance cover</b>	Abrasion, Weather	<b>Temp max</b>	80 °C
<b>Design</b>	Wrapped	<b>Color</b>	Black

### DESCRIPTION

Hose designed to be used for transportation of petroleum products with no more than 50% aromatic contents. Good to use on gas trucks, as well as on refineries. Equipped with an antistatic wire.

SKU	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14350014	22 mm	32 mm	1 MPa	165 mm	40 m	0.54 kg
14350016	25 mm	35 mm	1 MPa	250 mm	40 m	0.6 kg
14350018	28 mm	38 mm	1 MPa	240 mm	40 m	0.65 kg
14350020	32 mm	45 mm	1 MPa	320 mm	40 m	0.72 kg
14350022	35 mm	48 mm	1 MPa	350 mm	40 m	0.78 kg
14350024	38 mm	51 mm	1 MPa	380 mm	40 m	0.87 kg
14350026	42 mm	56 mm	1 MPa	340 mm	60 m	1.41 kg
14350030	45 mm	59 mm	1 MPa	420 mm	40 m	1.5 kg
14350032	50 mm	64 mm	1 MPa	500 mm	40 m	1.67 kg
14350040	63.5 mm	79 mm	1 MPa	650 mm	40 m	2.17 kg
14350048	75 mm	91 mm	1 MPa	750 mm	40 m	2.71 kg
14350064	100 mm	116 mm	1 MPa	820 mm	40 m	3.18 kg