



# 1438-60

## MULTIFLEX SUCTION AND PRESSURE HOSE

### Media



### SPECIFICATIONS

<b>Cover</b>	CR	<b>Media</b>	Oil, Gasoline
<b>Tube</b>	NBR	<b>Safety factor</b>	1:4
<b>Reinforcement</b>	Textile and steel spiral	<b>Temp min</b>	-30 °C
<b>Resistance cover</b>	Weather, Abrasion	<b>Temp max</b>	120 °C
<b>Design</b>	Corrugated	<b>Color</b>	Black

### DESCRIPTION

Suction and pressure hose for oil and gasoline with no more than 50% aromatic contents. The hose is corrugated which is a very good solution where there is a need for a flexible hose.

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil length	Weight
14386008	13 mm	22 mm	0.5 MPa	50	40 mm	20 m	0.32 kg
14386010	16 mm	24 mm	0.5 MPa	50	45 mm	20 m	0.39 kg
14386012	19 mm	27 mm	0.5 MPa	50	50 mm	20 m	0.43 kg
14386014	22 mm	31 mm	0.5 MPa	50	60 mm	20 m	0.49 kg
14386016	25 mm	34 mm	0.5 MPa	50	65 mm	20 m	0.55 kg
14386018	28 mm	35 mm	0.5 MPa	50	75 mm	20 m	0.59 kg
14386020	32 mm	41 mm	0.5 MPa	50	80 mm	20 m	0.65 kg
14386022	35 mm	43 mm	0.5 MPa	50	90 mm	20 m	0.7 kg
14386024	38 mm	46 mm	0.5 MPa	50	100 mm	20 m	0.74 kg
14386026	42 mm	50 mm	0.5 MPa	50	115 mm	20 m	0.8 kg
14386028	42 mm	50 mm	0.5 MPa	50	120 mm	20 m	0.82 kg
14386030	45 mm	53 mm	0.5 MPa	50	125 mm	20 m	0.86 kg
14386032	51 mm	60 mm	0.5 MPa	50	145 mm	20 m	1 kg
14386036	58 mm	66 mm	0.5 MPa	50	160 mm	20 m	1.38 kg
14386037	58 mm	66 mm	0.5 MPa	50	170 mm	20 m	1.19 kg
14386040	63.5 mm	72 mm	0.5 MPa	50	180 mm	20 m	1.52 kg
14386044	70 mm	79 mm	0.5 MPa	50	210 mm	20 m	1.75 kg
14386048	76 mm	85 mm	0.5 MPa	50	230 mm	20 m	1.99 kg

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil length	Weight
14386051	80 mm	90 mm	0.5 MPa	50	240 mm	20 m	2.03 kg
14386056	90 mm	102 mm	0.5 MPa	50	245 mm	20 m	2.78 kg
14386064	102 mm	114 mm	0.5 MPa	50	330 mm	20 m	2.72 kg
14386080	127 mm	144 mm	0.5 MPa	50	330 mm	20 m	4.08 kg