



1439-00

TANKOIL HW, TRUCK
HOSE WITH SPIRAL 10
BAR



Media



SPECIFICATIONS

Cover	NBR/SBR	Media	Oil, Gasoline
Tube	NBR	Safety factor	1:3
Reinforcement	Textile and steel spiral	Temp min	-35 °C
Resistance cover	Weather, Abrasion	Temp max	80 °C
Design	Wrapped	Color	Black

Related Item: 5020-00, 5020-10, 5020-20, 5020-30, 5021-00, 5021-10, 5021-20, 5021-30, 5022-00, 5022-10, 5022-20, 5022-25, 5022-30, 5022-50, 5023-00, 5023-10, 5023-20, 5023-25, 5023-30, 5024-00, 5024-10, 5024-20, 5024-30, 5024-50, 5025-00, 5025-10, 5025-20, 5025-30, 5026-00, 5026-10, 5026-20, 5026-25, 5026-30, 5027-00, 5027-10, 5027-20, 5027-30, 5050-xx, 5053-20, 5053-40, 5054-20, 5054-40, 5055-20, 5056-20

DESCRIPTION

Hose designed to be used for suction and pressure lines with petroleum products with no more than 50% aromatic contents, e.g. gas trucks, tank wagons and refineries. The strong design makes it usable in demanding environments and low temperatures. Electric resistance: 106 Ohm.

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
14390012	19 mm	29 mm	1 MPa	92	85 mm	40 m	0.58 kg
14390016	25 mm	35 mm	1 MPa	92	98 mm	40 m	0.7 kg
14390020	32 mm	43 mm	1 MPa	92	140 mm	40 m	0.96 kg
143900203	203 mm	221 mm	1 MPa	92	1100 mm	40 m	11.94 kg
14390024	38 mm	49 mm	1 MPa	92	170 mm	40 m	1.16 kg
14390032	51 mm	63 mm	1 MPa	92	250 mm	40 m	1.67 kg
14390040	63 mm	76 mm	1 MPa	92	310 mm	40 m	2.16 kg
14390048	76 mm	89 mm	1 MPa	92	380 mm	40 m	2.67 kg
14390064	102 mm	117 mm	1 MPa	92	510 mm	40 m	4.04 kg
14390080	127 mm	145 mm	1 MPa	92	650 mm	40 m	6.07 kg
14390096	152 mm	170 mm	2 MPa	92	790 mm	40 m	7 kg