



# 1440-00

## WELDARC, WELDING HOSE EN 559 ISO 3821 20 BAR BLUE OR RED



### Media



### SPECIFICATIONS

<b>Cover</b>	SBR/EPDM	<b>Media</b>	Gas and welding
<b>Tube</b>	SBR	<b>Safety factor</b>	1:3
<b>Reinforcement</b>	PE	<b>Standard</b>	ISO 3821
<b>Resistance cover</b>	Ozone, Weather	<b>Temp min</b>	-20 °C
<b>Design</b>	Smooth	<b>Temp max</b>	60 °C

### DESCRIPTION

Welding hose is suitable for all types of aggregates, high ignition temperature and low diffusion. It is very good air pressure hose and flexible even in low temperatures. According to the latest European Norm ISO 3821.

Item number	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight	Color
14400103	5 mm	12 mm	2 MPa	40 mm	50 m	0.11 kg	Red
14400104	6.3 mm	13.3 mm	2 MPa	40 mm	50 m	0.15 kg	Red
14400105	8 mm	15 mm	2 MPa	40 mm	50 m	0.17 kg	Red
14400106	10 mm	17 mm	2 MPa	50 mm	50 m	0.2 kg	Red
14400108	12.7 mm	21 mm	2 MPa	70 mm	50 m	0.42 kg	Red
14400112	20 mm	28 mm	2 MPa	150 mm	50 m	0.63 kg	Red
1440011290	19 mm	27 mm	2 MPa	150 mm	50 m	0.62 kg	Red
14400203	5 mm	12 mm	2 MPa	40 mm	50 m	0.13 kg	Blue
14400204	6.3 mm	13.3 mm	2 MPa	40 mm	50 m	0.15 kg	Blue
14400205	8 mm	15 mm	2 MPa	40 mm	50 m	0.18 kg	Blue
14400206	10 mm	17 mm	2 MPa	50 mm	50 m	0.2 kg	Blue
14400208	12.7 mm	21 mm	2 MPa	70 mm	50 m	0.36 kg	Blue
14400212	20 mm	28 mm	2 MPa	150 mm	50 m	0.67 kg	Blue
1440021290	19 mm	27 mm	2 MPa	150 mm	50 m	0.62 kg	Blue