



# 1450-10

## COBRA, CHEMICAL HOSE EPDM EN12115

### Media



### SPECIFICATIONS

<b>Cover</b>	EPDM	<b>Safety factor</b>	1:4
<b>Tube</b>	EPDM	<b>Standard</b>	EN 12115
<b>Reinforcement</b>	Synthetic textile, galvanized spiral and antistatic copper wire	<b>Temp min</b>	-40 °C
<b>Resistance cover</b>	Abrasion, Weather	<b>Temp max</b>	120 °C
<b>Design</b>	Wrapped	<b>Color</b>	Black
<b>Media</b>	Chemicals		

### DESCRIPTION

Suction and pressure hose for aggressive chemicals. used for loading and unloading of gas trucks, railroad cars, cargo liners and in stationary installations in chemical premises. The hose is flexible and resists external abrasion well. Electrical properties : type Ω/T according to norm EN 12115 (R<106 Ω, R<109 Ω through the hose wall)

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
14501012	19 mm	31 mm	1.6 MPa	90	65 mm	40 m	1.5 kg
14501016	25 mm	37 mm	1.6 MPa	90	90 mm	40 m	0.66 kg
14501020	32 mm	44 mm	1.6 MPa	90	120 mm	40 m	0.99 kg
14501024	38 mm	51 mm	1.6 MPa	90	155 mm	40 m	1.3 kg
14501032	50 mm	66 mm	1.6 MPa	90	215 mm	40 m	2.13 kg
14501040	63.5 mm	79.5 mm	1.6 MPa	90	275 mm	40 m	2.86 kg
14501048	75 mm	91 mm	1.6 MPa	90	330 mm	40 m	3.41 kg
14501064	100 mm	116 mm	1.6 MPa	90	450 mm	40 m	4.41 kg