



1456-10

ANACONDA, YELLOW HOSE 30 /25 BAR

Media



SPECIFICATIONS

Cover	EPDM	Media	Chemicals, Water, Air
Tube	EPDM	Safety factor	1:3
Reinforcement	Textile	Temp min	-40 °C
Resistance cover	Abrasion, Weather	Temp max	120 °C
Design	Smooth	Color	Yellow

DESCRIPTION

Very flexible hose with a wide temperature range. Well suited for air and hot and cold water. It is resistant towards lighter chemicals. It has good ozone resistance. 6-38mm have a smooth cover and 42-65mm have a wrapped cover. Electrically conductive tube construction prevents the build-up of static electricity. R 106 Ω AdBlue resistant. Temperature range -40°C / +120°C ; max. +100°C fluid temperature in closed systems.

Item number	ID	OD	Wp	Bend radii [mm]	Coil lenght	Weight
14561004	6 mm	14 mm	3 MPa	40 mm	100 m	0.18 kg
14561005	8 mm	17 mm	3 MPa	50 mm	100 m	0.26 kg
14561006	10 mm	20 mm	3 MPa	60 mm	100 m	0.34 kg
14561008	13 mm	23 mm	3 MPa	80 mm	100 m	0.41 kg
14561010	16 mm	27 mm	3 MPa	100 mm	50 m	0.55 kg
14561012	19 mm	30 mm	3 MPa	115 mm	50 m	0.63 kg
14561016	25 mm	37 mm	2.5 MPa	150 mm	50 m	0.87 kg
14561020	32 mm	44 mm	2.5 MPa	200 mm	50 m	1.14 kg
14561024	38 mm	51 mm	2.5 MPa	250 mm	50 m	1.4 kg
14561026	42 mm	56 mm	2.5 MPa	340 mm	40 m	1.56 kg
14561032	50 mm	66 mm	2.5 MPa	400 mm	40 m	2.03 kg
14561040	65 mm	83 mm	2.5 MPa	520 mm	40 m	2.71 kg