



1469-20

GAS TRUCK, HOSE EN12115, 16 BAR ANTISTATIC WIRE



Media



SPECIFICATIONS

Cover	CR	Safety factor	1:4
Tube	NBR	Standard	EN 12115
Reinforcement	Steel wire, Textile	Temp min	-30 °C
Resistance cover	Abrasion, Weather	Temp max	80 °C
Design	Wrapped	Color	Black
Media	Oil and gasoline		

Related Item: 5020-00, 5020-10, 5020-20, 5020-30, 5021-00, 5021-10, 5021-20, 5021-30, 5022-00, 5022-10, 5022-20, 5022-25, 5022-30, 5022-50, 5023-00, 5023-10, 5023-20, 5023-25, 5023-30, 5024-00, 5024-10, 5024-20, 5024-30, 5024-50, 5025-00, 5025-10, 5025-20, 5025-30, 5026-00, 5026-10, 5026-20, 5026-25, 5026-30, 5027-00, 5027-10, 5027-20, 5027-30, 5050-xx, 5053-20, 5053-40, 5054-20, 5054-40, 5055-20, 5056-20

DESCRIPTION

Gas truck hose fulfilling the requirements according to EN12115. The hose is designed to be used with petroleum products with no more than 55% aromatic contents. Designed with textile reinforcement with a twin spiral and two antistatic wires. Electric resistance: 106 Ohm. Vacuum = 90%. Oil, weather and abrasion resistant cover.

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
14692016	25 mm	37 mm	1.6 MPa	90	150 mm	40 m	0.8 kg
14692020	32 mm	44 mm	1.6 MPa	90	175 mm	40 m	0.98 kg
14692024	38 mm	51 mm	1.6 MPa	90	225 mm	40 m	1.14 kg
14692032	51 mm	67 mm	1.6 MPa	90	275 mm	40 m	1.69 kg
14692040	63.5 mm	80 mm	1.6 MPa	90	300 mm	40 m	2.87 kg
14692048	76 mm	92 mm	1.6 MPa	80	350 mm	40 m	3.36 kg
14692064	102 mm	118 mm	1.6 MPa	80	450 mm	40 m	4.7 kg