



1533-00

OIL SUCTION AND PRESSURE HOSE PVC



Media



SPECIFICATIONS

Cover	PVC/NBR	Media	Oil, Water
Tube	PVC/NBR	Safety factor	1:3
Reinforcement	PVC	Temp min	-25 °C
Resistance cover	Abrasion, Weather	Temp max	60 °C
Design	Slightly Corrugated	Color	Blue

DESCRIPTION

Super elastic oil resistant suction and pressure hose for paraffins, grease oils, mineral based hydraulic oils, diesel, sludge and water etc. Low weight and very flexible. Also available in antistatic design, see 1533-10.

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
15330012	19 mm	26 mm	0.8 MPa	90	100 mm	50 m	0.36 kg
15330016	25 mm	34 mm	0.7 MPa	90	115 mm	50 m	0.48 kg
15330020	32 mm	41 mm	0.6 MPa	90	130 mm	50 m	0.58 kg
15330024	38 mm	48 mm	0.6 MPa	90	140 mm	50 m	0.67 kg
15330032	51 mm	61 mm	0.7 MPa	90	200 mm	50 m	0.98 kg
15330040	63 mm	75 mm	0.5 MPa	90	275 mm	50 m	1.35 kg
15330048	76 mm	88 mm	0.5 MPa	90	310 mm	50 m	1.7 kg
15330064	102 mm	116 mm	0.4 MPa	80	410 mm	50 m	2.6 kg