



1554-55

DAIRSTREAM REVIVE, MILK HANDLING 6 BAR



Media



Certificate



SPECIFICATIONS

Cover	NR	Media	Food and beverage, Food
Tube	NR	Safety factor	1:3
Reinforcement	Thermoplastic wire, Textile	Temp min	-40 °C
Resistance cover	Abrasion, Weather	Temp max	80 °C
Design	Wrapped	Color	Blue

DESCRIPTION

Improved, crush-resistant version of the high-quality Dairystream milk and dairy hose is perfect for the collection and handling of milk and other dairy products. The thermoplastic helix used in this hose offers reliable crush resistance without the weight. This means it returns to its original shape after being squashed, and makes the Dairystream Revive 15% lighter than the standard Dairystream hose with a steel helix. It remains flexible even in cold outdoor conditions and provides milk tanker operators with a functional, easy-to-attach and ergonomic solution for loading bays. Hose that can be steam-cleaned at temperatures of up to 110°C and is also designed to withstand cleaning with most common detergents. It is a food-grade product that meets major food contact requirements and is phthalate-free.

Item number	ID	OD	Wp	Vacuum, max	Bend radii [mm]	Coil length	Weight
15545524	38 mm	52 mm	0.6 MPa	70	115 mm	40 m	1.15 kg
15545532	51 mm	65 mm	0.6 MPa	70	175 mm	40 m	1.45 kg
15545540	63 mm	77.5 mm	0.6 MPa	70	210 mm	40 m	1.8 kg
15545548	76 mm	92 mm	0.6 MPa	70	285 mm	40 m	2.4 kg