



1561-0x

EXHAUST HOSE FOR HOT AIR, NEOPRENE, SINGLE COATED



Media



SPECIFICATIONS

Cover	CR	Media	Ventilation
Tube	CR	Temp min	-35 °C
Reinforcement	Steel spiral	Temp max	135 °C
Resistance cover	Abrasion, Weather	Color	Black
Design	Wrapped		

DESCRIPTION

Hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and very flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

Item number	ID	Wp	Vacuum, max	Bend radii [mm]	Coil lenght	Weight
15610016	25 mm	0.15 MPa	5	17 mm	4 m	0.12 kg
15610020	32 mm	0.15 MPa	5	19 mm	4 m	0.13 kg
15610029	44 mm	0.15 MPa	5	26 mm	4 m	0.21 kg
15610032	51 mm	0.15 MPa	5	30 mm	4 m	0.25 kg
15610040	63 mm	0.13 MPa	5	36 mm	4 m	0.31 kg
15610048	76 mm	0.11 MPa	4	42 mm	4 m	0.41 kg
15610055	89 mm	0.11 MPa	4	49 mm	4 m	0.49 kg
15610064	102 mm	0.11 MPa	3	55 mm	4 m	0.65 kg
15610080	127 mm	0.09 MPa	2.1	69 mm	4 m	0.8 kg
15610096	152 mm	0.08 MPa	1.8	81 mm	4 m	0.99 kg
15610180	180 mm	0.06 MPa	1	94 mm	4 m	1.21 kg
15610203	203 mm	0.06 MPa	1	107 mm	4 m	1.39 kg
15610254	254 mm	0.04 MPa	1	132 mm	4 m	2 kg
15610305	305 mm	0.01 MPa	0.7	158 mm	4 m	2.41 kg